

**Technical Data Sheet****L 93 Everclear semi-gloss and matt****also applicable for Stop and Antistatic versions**

<b>Description</b>	L 93 Everclear is a water-based antiskid care product for finished parquet and hardwood flooring, finished cork surfaces, PVC and linoleum. L 93 Everclear Stop is a product with a special antiskid effect, its slip friction coefficient corresponds to DIN 18032 and should be used whenever increased non-skid properties of the floor are required. L 93 Everclear Antistatic reduces the electrostatic charge of finished hardwood flooring. L 93 Everclear should be used on floors with intact finish films only, otherwise the wood is liable to turn grey as a result of water penetration. Giscode GE 10.
<b>Note</b>	<p>As a rule, a finished hardwood floor should be treated with L 93 Everclear after 8-10 days only. The service life of the finish strongly depends on the careful treatment of the floor during the first days. Prior to the first intensive use at the latest, the floor must be treated as described under item „First and basic maintenance“. Depending on its use, every finish is subject to natural wear. For this reason, regular maintenance is absolutely essential. If the surface is damaged by use, the floor must be sanded and recoated. This measure is also part of the maintenance of finished hardwood floors and should be carried out in due time. Puddles should be avoided and saturated cloths or pads should not be left on the wooden flooring in order to avoid discolourations.</p> <p>Impregnated floors should be treated with Aqua-Satin Polish, L 92 Fitpolish or Superwax as they are liable to turn grey due to water penetration. Basic cleaning is necessary whenever the maintenance system is changed.</p>
<b>Application</b>	Shake well before use. L 93 Everclear can be used as follows:
<b>First and basic maintenance</b>	The first coat of L 93 Everclear after finishing or basic cleaning is evenly applied to the parquet or hardwood floor in a thin layer. Consumption: abt. 30-40 ml/sq.mtr. (undiluted). Use lintfree cloths or our special wiper ("Wischwiesel") for application.
<b>Basic cleaning</b>	L 93 Everclear forms a film on the floor. Depending on the frequency and intensity of maintenance, the film must be removed either manually or by means of a machine using L 94 Cleaner / Wax-Remover. Generally, basic cleaning is required whenever the floor is unsightly or heavily soiled with impurities which cannot be removed by normal cleaning.
<b>Important advice</b>	Do not soak the floor with water during maintenance or basic cleaning as swelling of the wood may lead to damages.
<b>Storage / transport</b>	Shelf life of original unopened packing min. 24 months provided that material is transported and stored at a cool and dry place protected from freezing.
<b>Industrial-coated prefinished hardwood floors</b>	The adhesion of L 93 Everclear on prefinished hardwood and laminate floors must be tested from case to case. Joint protection using Fill-and-Finish may be necessary. Please also observe the recommendations of the prefinished hardwood floor manufacturers.
<b>Cross reference</b>	The following Technical Data Sheets should be observed: - General instructions of use for hardwood floor finishing products - Cleaning and maintenance of finished/oiled floors - Identification and safety instructions (MSDS)

Date of issue 07/07